


## Please Note that PVDF Colours are Special Order Only

PVDF (Polyvinylidene Fluoride) is a highly non-reactive and pure thermoplastic fluoropolymer used in a variety of applications where the highest purity, strength, and resistance to solvents, acids, bases, and heat are required. PVDF pre-painted steel is best suited for high-end applications such as commercial or residential roofing, pre-engineered buildings, architectural wall panels, facades, and other applications where durability and long-lasting performance are required.




REGAL WHITE  
SRI: 78



PARCHMENT  
SRI: 58



SIERRA TAN  
SRI: 58



CHAMPAGNE METALLIC  
SRI: 49



MOCHA  
SRI: 35




WEATHERED COPPER  
SRI: 27



BRONZE  
SRI: 25



DARK BRONZE  
SRI: 27



COPPER PENNY  
SRI: 42



TERRA COTTA  
SRI: 42



COLONIAL RED  
SRI: 34



RETRO RED  
SRI: 25



HEMLOCK GREEN  
SRI: 37



FOREST GREEN  
SRI: 30



HARTFORD GREEN  
SRI: 27



BLACK  
SRI: 24




SILVER METALLIC  
SRI: 58



TWILIGHT BLUE  
SRI: 25



REGAL BLUE  
SRI: 25



WEATHERED ZINC  
SRI: 40




OLD TOWN GREY  
SRI: 42



OLD ZINC GREY  
SRI: 40



SLATE GREY  
SRI: 30



ZINC GREY  
SRI: 37

**The Solar Reflectance Index (SRI)** is a measure of the roof's ability to reject solar heat, as shown by a small temperature rise. SRI is a gauge from 0-100, with 0 being most likely to absorb and radiate heat (such as a tar roof) and 100 being the most reflective (least likely to get hot)